



## HUNT *Simplicity*<sup>®</sup> FD Series Modular Dimming Systems for dimming T12 F40 lamps with Compatible Dimming Ballasts 120 or 277 Volts



**FD-20/FD-27**



**FD-30**

Hunt Control Systems Inc.  
200 Rome Court  
Fort Collins CO 80524

### Features:

- Continuous, flicker-free dimming
- Manually operates 1- and 2-lamp compatible electromagnetic dimming ballasts
- Master units can control up to (15) FD-20-S, FD-30-S, or FD-27-S slave units from a single 4-wire, single-gang control
- Limited one-year warranty
- UL Listed

### Specifications:

- For use with approved ballasts only (see below)
- Wall-mounted, convection-cooled
- Use T12 F40 lamps only
- Requires remote control switch, preset slide and rotary available, single pole or 3-way

Tel: (970) 484-9048  
Fax: (970) 493-4125  
huntedimming.com

### Approved Ballasts:

### Maximum Number of Lamps

<u>Manufacturer &amp; Model</u>	<u>FD-20</u>	<u>FD-30</u>	<u>FD-27</u>
Universal 550-L-TC-P	38	50	--
Universal 502-A-TC-P	38	56	--
GE/Valmont 8G5001	38	50	--
GE/Valmont 8G5007	38	56	--
Advance DIM-140-H-TP	32	48	--
Advance DIM-240-H-TP	32	48	--
Universal 679-L-TC-P	--	--	40
Universal 678-A-TC-P	--	--	40


## Dimming.

It's all we do.  
Since 1960.


### Dimensions:

FD-20, FD-27: 10"H x 8 1/2"W x 3 3/4"D  
FD-30: 11 1/2"H x 8 1/2"W x 3 3/4" D

## HUNT *Simplicity*<sup>®</sup> FD Series Modular Dimming Systems for dimming T12 F40 lamps with Compatible Dimming Ballasts 120 or 277 Volts



**FD-20-S/FD-27-S**



**FD-30-S**

Hunt Control Systems Inc.  
200 Rome Court  
Fort Collins CO 80524

### Features:

- Continuous, flicker-free dimming
- Manually operates 1- and 2-lamp compatible electromagnetic dimming ballasts
- Up to (15) slave units per each master unit (FD-20, FD-30, FD-27) controlled from a single 4-wire, single-gang control
- Limited one-year warranty
- UL Listed

### Specifications:

- For use with approved ballasts only (see below)
- Must be connected to FD-20, FD-30, or FD-27 master unit
- Wall-mounted, convection-cooled
- Use T12 F40 lamps only
- Requires remote control switch, preset slide and rotary available, single pole or 3-way

Tel: (970) 484-9048  
Fax: (970) 493-4125  
huntdimming.com

### Approved Ballasts:                      Maximum Number of Lamps

<u>Manufacturer &amp; Model</u>	<u>FD-20-S</u>	<u>FD-30-S</u>	<u>FD-27-S</u>
Universal 550-L-TC-P	38	50	--
Universal 502-A-TC-P	38	56	--
GE/Valmont 8G5001	38	50	--
GE/Valmont 8G5007	38	56	--
Advance DIM-140-H-TP	32	48	--
Advance DIM-240-H-TP	32	48	--
Universal 679-L-TC-P	--	--	40
Universal 678-A-TC-P	--	--	40

### **Dimming.**

It's all we do.  
Since 1960.

### Dimensions:

FD-20-S, FD-27-S: 10"H x 8 1/2"W x 3 3/4"D  
FD-30-S: 11 1/2"H x 8 1/2"W x 3 3/4" D

## HUNT *Simplicity*<sup>®</sup> PS-IFC-1 Series Controls for ID and FD Series Modular Systems 120V and 277V



PS-IFC-1  
PS-IFC-1-3W

Hunt Control Systems Inc.  
200 Rome Court  
Fort Collins CO 80524

Tel: (970) 484-9048  
Fax: (970) 493-4125  
[huntedimming.com](http://huntedimming.com)

### **Features:**

- Preset slide control – strap mount.
- Easy-to-operate, smooth-sliding linear control and switch.
- Available in single-pole or 3-way.
- Uses standard designer-style faceplate, included in box.
- Fits in any standard 2" deep single gang switchbox.
- Limited one-year warranty.
- Available in Ivory, White (standard colors), Brown, Black or Gray (custom colors).
- Rated for 120/277V applications.

### **Note:**


All 3-way controls require a standard 3-way toggle switch to complete the circuit.

### **Dimming.**


It's all we do.  
Since 1960.

**Wiring Diagram  
For HUNT *Simplicity*<sup>®</sup>  
PS-IFC-1, AIFC-1 and PS-IFC-3W-1  
Controls for ID and FD Series**

**Single Pole Wiring**



**Three Way Wiring**



**Hunt Control Systems, Inc.**  
200 Rome Court  
Fort Collins, CO 80524  
U.S.A  
Ph: (970) 484-9048  
Fax: (970) 493-4125  
[www.hunt dimming.com](http://www.hunt dimming.com)